	ت D			0	B		,
4	M Thread	ØF F F F F F F F F F F F F F F F F F F					4
ω				LAYOUT SHOWN AS EXAM	1PLE		3
		Keying Shown as example					
	CHARACTERISTICSStandard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal					
	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	F22.25 MaxZ31.5 MaxVV THREADM18x1-6g		SOURIAU shall not be liable for any no due to a use of the Products which the Specifications issued by either of the (professional recommendation,	hich does not comply with of the Parties or by a third party		
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum			Country FR	Jurisdiction & Control List Not Listed		2
	Durability : 500 Mating cycles Delivered with Souriau contacts and Accessories			PN: 8D113W98BB			
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 27-09-2	016 First Release			
			ISS DATE Designed By:	E Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
			TITLE	Aluminium Ir	nline plug 8D series		
_	BASIC SERIES: 8D 1 - 13 W SHELL TYPE : In line Receptacle I	98 B B	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		1
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : B			- SOURIAU WWW.SOURIAU.COM It must not be			
	SHELL SIZE : 13 PLATING : W = Olive drab Cadmium	CONTACT TYPE : SOCKET(YOUT : 13-98 FORMAT	SOURIAU D	communicated without perr	mission SHEET	
			A3	8D113W98	BB-C	1/2	
	H G I	F I E \		C	B I A		

ſ	D I	г	п	D	C B			
	Contact Layout							
4	$\begin{array}{c} & & & & \\ & & & & \\ & & & \\ & & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\$							4
	(Insert arrangement 13-98) Location Contact position ID Location X-axis (mm) (mm) A +.000 (0.00) +.195 (4.95) B +.125 (3.18) +.150 (3.81) C +.193 (4.90) +.030 (0.76) D 104 (4.17) 105 (2.67) E +.000 (0.00) 135 (3.43) F 164 (4.17) 105 (2.67)						-	
	G 193 (4.90) +.030 (0.76) H 125 (3.18) +.150 (3.81) J +.065 (1.65) 015 (0.38) K 065 (1.65) 015 (0.38)							
င်သ	Shell sizeArrangement no.Number oSize contactsService ratingContact locationSupersedes13-981020IAllMS20051-98							3
					SOURIAU shall not be liable for any non-conf due to a use of the Products which does n the Specifications issued by either of the Partie (professional recommendation, techni	ot comply with s or by a third party		
N					Country J FR	urisdiction & Control List Not Listed		2
					PN: 8D113W98BE	3		
				A 27-09-2016 Fi	irst Release			
				ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	—
				TITLE	Aluminium Inline	plug 8D series		
_				SCALE	General linear Tolerances: ±	NPRDS / PROJECT 859		1
				SOURIAU	WWW.SOURIAU.COM	This document is the prop SOURIAU it must not be reproduce communicated without per	ed or	'
				FORMAT	SOURIAU DRG	N°	SHEET	
		-	_	A3	8D113W98BB-		2/2	
	H I G I	F	I E \	D	C I B	I A		