ſ	T G	т п	D	0	B				
4	Z Thread Thr	ØF Image: Constrained and the second				4			
ω				LAYOUT SHOWN AS EXAM	IPLE	3			
		Keying Shown as example							
	CHARACTERISTICSStandard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal							
	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	F22.25 MaxZ31.5 MaxVV THREADM18x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)					
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum			Country FR	Jurisdiction & Control List Not Listed	2			
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D113W98BA					
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 27-09-2	2016 First Release					
			ISS DAT Designed By:	E Latest modification - by Date:	CUSTOMER DRAWING	MOD N°			
			TITLE	Aluminium Ir	nline plug 8D series				
_	BASIC SERIES: 8D 1 - 13 W SHELL TYPE : In line Receptacle I	98 B A	SCALE	General linear Tolerances:	NPRDS / PROJECT 859				
	CONTACT TYPE : Standard Crimp Contact	ORIE		SOURIAU This document is the property of SOURIAU SOURIAU it must not be reproduced or					
	SHELL SIZE : 13 PLATING : W = Olive drab Cadmium	CONTACT TYPE : SOCKET(5		SOURIAU D	communicated without perr				
			A3	8D113W98		1/2			
L	H G	F E	D	С	BA				

	Т	۵	П	п	D	0	ω	А		
		Contact Layout								
4		$\begin{array}{c} & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ &$								4
		Location Contact osition ID X-axis (mm) Y-axis (mm) A +.000 (0.00) +.195 (4.95) B +.125 (3.18) +.150 (3.81) C +.193 (4.90) +.030 (0.76) D 104 (4.17) 105 (2.67) E +.000 (0.00) 135 (3.43) F 164 (4.17) 105 (2.67) G 193 (4.90) +.030 (0.76) H 125 (3.18) +.150 (3.81) J +.065 (1.65) 015 (0.38) K 065 (1.65) 015 (0.38)								
ω	Shell sizeArrangement no.13-98	Number of contacts Size contacts Service rating Contact location Supers 10 20 I All MS200								3
	_									
						SOURIAU shall not be liable for any due to a use of the Products wh the Specifications issued by either of (professional recommendat)	ich does not comply wi the Parties or by a thir	th		
N						Countr	/ Jurisdiction & Not Li			2
						PN: 8D113W98BA				
					A 27-09-2016	5 First Release				
					ISS DATE Designed By:	Latest modification - by Date:	CUST	M DMER DRAWING	10D N°	
					TITLE	Aluminium	Inline plug 8D s	series		
					SCALE -	General linear Tolerances:	NP	RDS / PROJECT		
<u> </u>					NA	<u>±</u>	Tł	859	of	1
					SOURIAU	WWW.SOURIAU.C		SOURIAU it must not be reproduced or nmunicated without permission		
					FORMAT	SOURIAU			SHEET	
l			-		A3	8D113W			2/2	
	Н	G	I F	I E	D	C	В	A		