






REV.	DATE	ECR NO.	DESCRIPTION
NC	12/17/09	XXXXXX	INITIAL RELEASE



RECOMMENDED
CABLE STRIPPING DIM'S



1. CRIMPED FERRULE
HEX CRIMP SIZE .151"
2. CRIMPED CONTACT PIN
SQ. CRIMP SIZE 0.7mm

9			1
8			1
7	HEAT SHRINK TUBING	BLACK	1
6	FERRULE	COPPER	1
5	CONTACT PIN	BRASS	1
4	BARREL	BRASS	1
3	INSULATOR	PTFE	1
2	INSULATOR	PTFE	1
1	BODY	BRASS	1
DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 - 8mm ± 0.20mm
8 - 30mm ± 0.40mm
30 - 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 - .315 = ± 0.007"
.315 - 1.180 = ± 0.015"
1.180 - 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN C.WANG	12/17/09
CHECKED	
ISSUED	
SHEET 1 OF 1	
CAD FILE C:/CONNEX/142190.DWG	

<h1>Amphenol Connex</h1>			
PART DESCRIPTION SMB CRIMP JACK (FOR RG-316U/D)			
PART NO. 142190			
DWG. NO.	142190.DWG	REV.	NC
SIZE	A	SCALE	NA